

TurfRx Fairway+

INCREASES ROOT DEVELOPMENT,
MICROBIAL DIVERSITY & RESPIRATION

Redox

GUARANTEED ANALYSIS

Total Nitrogen (N).....1%
 0.25%.....Ammoniacal Nitrogen
 0.25%.....Nitrate Nitrogen
 0.5%.....Urea Nitrogen
 Available Phosphate (P₂O₅).....7%
 Soluble Potash (K₂O).....12%
 ALSO CONTAINS NON-PLANT FOOD INGREDIENTS
 2%.....Humic Acid



REDOX TECHNOLOGY Complexed & Chelated Technology

WHY ?

TurfRx Fairway+ is a phosphorus and potassium fertilizer, containing proprietary soluble carbon compounds. **TurfRx Fairway+** reduces abiotic stress, improves root development and increases soil microbial diversity due to humic, fulvic, and long-chain soluble carbon content. **TurfRx Fairway+** utilizes technology from its proprietary TurfRx formulations of **P+**, **K+**, and **C-85**.

PRODUCT USAGE

Practical rates of use:	Apply TurfRx Fairway+ at 5 – 15L / Ha in 400 – 800L of water.
-------------------------	---

Higher rates than this are purely for extreme conditions where they are warranted.

A common agronomic situation would be low humus, low potassium levels and low levels of available phosphate; not high levels of phosphate tied up in the soil. The history of soil sampling has taught us this. TurfRx Fairway+ can assist the turf manager in addressing this type of situation. An all-round package of a product: three proven Redox proprietary formulations in a single product.



HANDLING GUIDELINES

PRE-MIXING

Pre-mixing is considered a best practice when sprayer agitation is not optimum. Proper hydration is essential for all applications. Recirculate or agitate while adding material.

ONCE THE MATERIAL IS ADDED TO WATER, CONSTANT AGITATION IS REQUIRED.

COMPATABILITY

Always jar test first.

Redox products are compatible with other Redox products when following product handling guidelines.

Use caution with reactive materials. For example, phosphorus and calcium.

Avoid extreme shifts in tank pH. When utilizing Redox materials that acidify, check tank pH prior to adding buffers.

TANK MIXING/INJECTION

Use of an anti-foaming agent is recommended. Fill the tank 50% full with water and initiate tank agitation prior to adding materials.

Don't add material too quickly—this allows for more thorough hydration.

The use of inductor assemblies is encouraged.

Recirculate or agitate while adding material.

ONCE THE MATERIAL IS ADDED TO WATER, CONSTANT AGITATION IS REQUIRED.

Rinse after use.

REFER TO PRODUCT HANDLING GUIDELINES FOR ADDITIONAL MIXING INSTRUCTIONS.