



INCREASES ROOT DEVELOPMENT,  
MICROBIAL DIVERSITY & RESPIRATION



**GUARANTEED ANALYSIS**

- Total Nitrogen (N).....1%
  - 0.25%.....Ammoniacal Nitrogen
  - 0.25%.....Nitrate Nitrogen
  - 0.5%.....Urea Nitrogen
- Available Phosphate (P<sub>2</sub>O<sub>5</sub>).....7%
- Soluble Potash (K<sub>2</sub>O).....12%
- ALSO CONTAINS NON-PLANT FOOD INGREDIENTS
- 2%.....Humic Acid



**WHY Fairway+ ?**

**TurfRx Fairway+** is a phosphorus and potassium fertilizer, containing proprietary soluble carbon compounds. **TurfRx Fairway+** reduces abiotic stress, improves root development and increases soil microbial diversity due to humic, fulvic, and long-chain soluble carbon content. **TurfRx Fairway+** utilizes technology from its proprietary TurfRx formulations of **P+**, **K+**, and **C-85**.

**PRODUCT USAGE**

Turf Performance	Apply 1.5-9 oz./1000 ft <sup>2</sup> (4.8-29 L/Ha) as a foliar/soil application every 1 to 6 weeks. Water in.
Grow-in	Apply 1.5-9 oz./1000 ft <sup>2</sup> (4.8-29 L/Ha) as a soil application at seeding/sprigging. Repeat every 2 to 5 weeks. Water in.
Aerification	Apply 1.5-9 oz./1000 ft <sup>2</sup> (4.8-29 L/Ha) as a soil application prior to aerification and repeat post-aerification. Water in.
Abiotic Stress Defense	Apply 1.5-9 oz./1000 ft <sup>2</sup> (4.8-29 L/Ha) as a foliar/soil application every 1 to 6 weeks. Water in.
Heat Stress	Apply 1.5-9 oz./1000 ft <sup>2</sup> (4.8-29 L/Ha) as a foliar/soil application every 1 to 6 weeks. Water in.
Thatch Reduction	Apply 1.5-9 oz./1000 ft <sup>2</sup> (4.8-29 L/Ha) as a soil application every 1 to 6 weeks. Water in.
Root Development	Apply 1.5-9 oz./1000 ft <sup>2</sup> (4.8-29 L/Ha) as a soil application every 1 to 6 weeks. Water in.

## HANDLING GUIDELINES

### PRE-MIXING

Pre-mixing is considered a best practice when sprayer agitation is not optimum. Proper hydration is essential for all applications. Recirculate or agitate while adding material.

**ONCE THE MATERIAL IS ADDED TO WATER, CONSTANT AGITATION IS REQUIRED.**

### COMPATIBILITY

Always jar test first.

Redox products are compatible with other Redox products when following product handling guidelines.

Use caution with reactive materials. For example, phosphorus and calcium.

Avoid extreme shifts in tank pH. When utilizing Redox materials that acidify, check tank pH prior to adding buffers.

### TANK MIXING/INJECTION

Use of an anti-foaming agent is recommended. Fill the tank 50% full with water and initiate tank agitation prior to adding materials.

Don't add material too quickly—this allows for more thorough hydration.

The use of inductor assemblies is encouraged.

Recirculate or agitate while adding material.

**ONCE THE MATERIAL IS ADDED TO WATER, CONSTANT AGITATION IS REQUIRED.**

Rinse after use.

*REFER TO PRODUCT HANDLING GUIDELINES FOR ADDITIONAL MIXING INSTRUCTIONS.*