

TurfRx Supreme

INCREASES NITROGEN METABOLISM

Redox

GUARANTEED ANALYSIS

Available Phosphate (P ₂ O ₅)	5%
Soluble Potash (K ₂ O)	4%
Boron (B).....	0.14%
Copper (Cu)	0.3%
Iron (Fe).....	0.3%
Manganese (Mn)	0.6%
0.6%...Water Soluble Manganese (Mn)	
Molybdenum (Mo)	0.005%
Zinc (Zn)	0.6%



WHY **TurfRx Supreme** ?

TurfRx Supreme is specifically formulated to target plant sugar alcohol production related to nitrogen metabolism in plants. The combination of plant nutrients and increased sugar alcohols will enhance nitrogen metabolism and improve overall quality and performance.

PRODUCT USAGE

Nitrogen Metabolism	Apply 0.75-3 oz./1000 ft ² (2.4-9.5 L/Ha) as a foliar/soil application. Apply every 1 to 4 weeks.
Turf Performance	Apply 0.75-3 oz./1000 ft ² (2.4-9.5 L/Ha) as a foliar/soil application. Apply every 1 to 4 weeks.
Spring Green-up	Apply 1.5-6 oz./1000 ft ² (4.8-19 L/Ha) as a foliar/soil application. Apply every 1 to 4 weeks.



INCREASES NITROGEN METABOLISM

Redox

HANDLING GUIDELINES

PRE-MIXING

Pre-mixing is considered a best practice when sprayer agitation is not optimum. Proper hydration is essential for all applications. Recirculate or agitate while adding material.

ONCE THE MATERIAL IS ADDED TO WATER, CONSTANT AGITATION IS REQUIRED.

COMPATABILITY

Always jar test first.

Redox products are compatible with other Redox products when following product handling guidelines.

Use caution with reactive materials.

Avoid extreme shifts in tank pH. When utilizing Redox materials that acidify, check tank pH prior to adding buffers.

TANK MIXING

Use of an anti-foaming agent is recommended. Fill the tank 50% full with water and initiate tank agitation prior to adding materials.

Don't add material too quickly—this allows for more thorough hydration.

The use of inductor assemblies is encouraged.

Recirculate or agitate while adding material.

Total foliar spray content of dry soluble Redox product should not exceed 2% solution (by weight).

If material is not applied immediately, tank recirculation is required prior to application to ensure uniform product distribution.

ONCE THE MATERIAL IS ADDED TO WATER, CONSTANT AGITATION IS REQUIRED.

REFER TO PRODUCT HANDLING GUIDELINES FOR ADDITIONAL MIXING INSTRUCTIONS.